

# Software Engineering

## *Detailed Design*

**Peter Müller**

Chair of Programming Methodology

The slides in this section are partly based on the lecture  
“Software Engineering I” by Prof. Bernd Brügge, TU München

Spring Semester 10

**ETH**

Eidgenössische Technische Hochschule Zürich  
Swiss Federal Institute of Technology Zurich

# 5. Detailed Design

## 5.1 Overview

## 5.2 Reuse

### 5.2.1 Design Patterns

### 5.2.2 Case Study: Patterns in the Java AWT

## 5.3 Interface Specification

## 5.4 Object Model Restructuring and Optimization

# Bloopers

- Speed
  - Harry's partner shoots Harry in the right leg
  - Throughout the movie, Harry limps on the left leg
  
- Star Wars
  - At the end of Episode V, Han Solo is frozen into carbonite
  - When being frozen, Han Solo is wearing a dark jacket
  - When thawed, he is wearing a white shirt

# Why do Movies Contain Bugs?

Scenes shot  
out of  
sequence


High pressure  
of release date  
during editing

Details (props,  
costumes)  
changed during  
production


Cooperation of  
many different  
people

Some scenes  
re-shot out of  
schedule

# Waterfall Model of Project Life Cycle




# Detailed Design: Closing the Gap



# Detailed Design

- **Adding details** to the requirements analysis and system design, and making **implementation decisions**
- **Choosing** among different ways to implement the analysis model and system design
  - Goals: minimize execution time, memory, and other measures of cost
- Providing the **basis for implementation**

# Detailed Design Activities



# Software Systems Often Face Similar Problems

Classes implemented independently


High pressure of release date

Details (interfaces, contracts) changed during development


Cooperation of many different people

Some classes re-designed out of schedule

# Detailed Design Activities (cont'd)



# Detailed Design Activities (cont'd)



# 5. Detailed Design

## 5.1 Overview

## 5.2 Reuse

### 5.2.1 Design Patterns

### 5.2.2 Case Study: Patterns in the Java AWT

## 5.3 Interface Specification

## 5.4 Object Model Restructuring and Optimization


## Implementation of Application Domain Objects

- New classes are often needed during detailed design
- The implementation of algorithms may necessitate objects to hold values (e.g., arrays)
- New low-level operations may be needed during the decomposition of high-level operations

# Application vs. Solution Objects: Example


## Requirements Analysis

(Language of application domain)



## Detailed Design

(Language of solution domain)



# Application vs. Solution Objects

- Application objects
  - Also called domain objects
  - Represent relevant **concepts of the domain**
  - Are identified by application domain specialists and by end users
- Solution objects
  - Represent concepts that have **no counterpart in the application domain**
  - Are identified by developers
  - Examples: persistent data stores, user interface objects, middleware

## Finding Solution Objects

*“Many objects in a design come from the analysis model. But object-oriented designs often end up with classes that have no counterparts in the real world. [...] Strict modeling of the real world leads to a system that reflects today's realities but not necessarily tomorrow's. The abstractions that emerge during design are key to making a design flexible.”*

[Gamma et al., 1995]

- There is a need for **reusable** and **flexible** designs
- **Design knowledge** complements application domain knowledge and solution domain knowledge

## Design Patterns

*“Design patterns help you identify less-obvious abstractions and the objects that can capture them. For example, objects that represent a process or algorithm don't occur in nature, yet they are a crucial part of flexible design. [...] These objects are seldom found during analysis or even the early stages of design; they're discovered later in the course of making a design more flexible and reusable.”*

[Gamma et al., 1995]

# Composite Pattern: Motivation

- A program manipulates
  - Individual units (e.g., graphical objects)




- Groups of units




- Wanted: a design that allows algorithms to deal with single units and groups in a uniform way

# Composite Pattern: Example




# Composite Pattern: Structure



- Allows hierarchical grouping of components

# Composite Pattern: Statement Syntax



# Composite Pattern: Properties

- Defines class hierarchies consisting of **primitive** objects and **composite** objects
  - Objects can be composed hierarchically
  - Composite objects can be used like primitive objects
- Makes client simple
- Makes it easier to add new kinds of components
- Can make the design overly general
  - Difficult to restrict composites
  - Example: no **return** statement in a block

# Floral Patterns



# Composite Pattern: Implementation Issues

- Explicit parent references
  - Simplifies traversal and deletion of components
- Sharing components
  - Reduces storage requirements
- Child ordering
  - Might be required by the design (e.g., Block Statement)
- Caching to improve performance
  - Improves performance (e.g., bounding box for Group)
- Data structure for storing components
  - Affects performance (lists, trees, arrays, hash tables)

# Abstract Factory Pattern: Motivation

- A client class wants to create sockets for network communication

Client

Socket


- The concrete implementation of the socket depends on the operating system

Windows  
Socket


Unix  
Socket

- The client class should be platform-independent

# Abstract Factory Pattern: Example



# Abstract Factory Pattern: Structure




# Abstract Factory Pattern: Properties



- Isolates concrete classes
  - Helps control what classes are instantiated
  - Isolates clients from implementation classes (clients manipulate objects through interfaces)
  
- Makes exchanging product families easy
  - Class of concrete factory appears only once in program
  
- Supporting new kinds of products is difficult
  - Affects interface of abstract factory and all concrete factories

# Observer Pattern: Motivation


- Maintaining **consistency** between **loosely coupled** objects
- Many dependent objects have to be informed when one object changes its state




	a	b	c
X	60	30	10
Y	50	30	20
Z	80	10	10



# Observer Pattern: Structure



# Observer Pattern: Collaborations





# Observer Pattern: Properties

- Abstract coupling between subject and observer
  - Subject does not know concrete class of observer
- Support for broadcast communication
  - Freedom to add and remove observers
  
- Example
  - Debuggers (subject) broadcasts event when it reaches a breakpoint
  - Editor (observer) shows line of code
  - Stack tracer (observer) shows stack trace.


## Strategy Pattern: Motivation

- A program uses 3D-shapes that can be rendered
  - Rendering code too complex to be included in Shape
- **Different** rendering **algorithms** are appropriate at different times
  - Do not implement the ones we do not use




- Rendering algorithm should **not** be **hard-wired**
  - New algorithms may be added

# Strategy Pattern: Example



# Strategy Pattern: Structure




# Strategy Pattern: Properties

- Supports families of algorithms
  - Sorting, line breaking, layouting, etc.
  - Clients have a choice (e.g., different space and time trade-offs)
  
- Alternative to inheritance
  - Behavior not hard-wired into context (dynamic exchange)
  - Separates context from algorithm (easier to maintain)
  
- Communication overhead
  - Arguments must be passed to strategies


# Adapter Pattern: Motivation

- A program expects an **interface** that **is incompatible** with the interface of a reusable class




- Common problem with legacy code
- Also known as **wrapper**

# Adapter Pattern: Example



# Adapter Pattern: Structure





- **Delegation** used to bind Adapter and Adaptee
- Subtyping used to specify interface of Adapter
- Target and Adaptee exist before Adapter
- Target may be realized as interface in Java

# Adapter Pattern: Properties


- How much adaptation does an adapter do?
  - From simple interface conversion (renaming) to entirely different set of operations
  
- Variant: class adapter
  - Adapter inherits from Target and Adaptee
  - No aggregation and delegation
  - Requires multiple inheritance if Target is a class

# Bridge Pattern: Motivation


- A program uses socket abstractions to communicate
- Different socket abstractions
- Different socket implementations




## Bridge Pattern: Motivation (cont'd)



# Bridge Pattern: Example



# Bridge Pattern: Structure




- **Decouples** an abstraction from its implementation
- Allows different **implementations** of an interface to be **exchanged dynamically**

## Adapter vs. Bridge

- Both are used to hide the details of the underlying implementation
- Adapter pattern
  - Makes **unrelated components** work together
  - Applied to systems **after they are designed** (reengineering, interface engineering)
- Bridge Pattern
  - **Used up-front in a design** to let abstractions and implementations vary independently
  - Green field engineering of an “extensible system”


# Facade Pattern: Motivation

- Subsystem 1 can call operations on any component of Subsystem 2
- Advantages
  - Efficiency
- Disadvantages
  - Caller does not understand how the subsystem works
  - Subsystem will be misused, leading to non-maintainable code



# Facade Pattern: Example

- Provides a unified interface to a set of objects in a subsystem
- Defines a higher-level interface that makes the subsystem easier to use
- **Reduces coupling**
- Does not prevent direct usage of objects in a subsystem



# Subsystem Design with Facade and Adapter

- Ideal structure of a subsystem
- An interface object (boundary object)
- A set of application domain objects (entity objects) modeling real entities or existing systems
  - Some of the entity objects are interfaces to existing systems
- One or more control objects

Facade

Interface to existing systems: Adapter


- Provides interface to existing system
- Existing system is not necessarily object-oriented!

# Design Patterns Encourage Reusable Designs


- **Facade** should be used by **all subsystems**
  - Defines all the services of the subsystem
  - Delegates requests to components within the subsystem
  - Most of the time the facade need not be changed when the component is changed
- **Adapters** should be used to **interface** to **existing components**
- **Bridges** should be used to interface sets of objects
  - Where the full set is not completely known at design time
  - When the subsystem must be extended later after the system has been deployed (dynamic extension)

# The “Ingredients” of Design Patterns

- Inheritance (subclassing)
  - Establishes **“is-a” relation**
  - Enables subtype **polymorphism**




- Aggregation
  - Establishes **“has-a” relation**
  - **No subtyping** in general




- Design patterns provide guidance how to use inheritance and aggregation

# Inheritance and Aggregation: Bridge Pattern



# Textual Clues in Nonfunctional Requirements

- Use textual clues to identify design patterns
  - (similar to Abbot's technique in analysis)



# 5. Detailed Design

## 5.1 Overview

## 5.2 Reuse

### 5.2.1 Design Patterns


### **5.2.2 Case Study: Patterns in the Java AWT**

## 5.3 Interface Specification

## 5.4 Object Model Restructuring and Optimization



# AWT: Overview

- AWT: Abstract Window Toolkit
- Elements of the GUI are represented by **components**
- **Display** and **layout** of the components have to be specified
- Components receive **events** from the window system and propagate them to so-called **listeners**




# Component Hierarchy: Composite Pattern

- Components can be grouped into containers
- Containers are also components




# Event Communication

- Objects can register at a component as observer (listener) for one or several event types
- Upon occurrence of an event, the event source informs all registered objects by invoking a method




# Component / Listener: Observer Pattern




# Platform Independence: Bridge Pattern

- AWT components are platform-independent
- Operations that depend on the window system are delegated to platform-specific peer objects




# Platform Independence: Peer Creation

- Component objects have references to their peers




- Platform-independent components cannot instantiate platform-dependent peers




- Solution: abstract factory

# Platform Independence: Abstract Factory




# Displaying Containers: Layout Managers


- Layout of components in one container is computed by a layout manager
- The layout manager can be set for each container




Border-  
Layout



Flow-  
Layout



# Layout Managers: Strategy Pattern



# 5. Detailed Design

## 5.1 Overview

## 5.2 Reuse

### 5.2.1 Design Patterns

### 5.2.2 Case Study: Patterns in the Java AWT

## **5.3 Interface Specification**

## 5.4 Object Model Restructuring and Optimization

# Specifying Interfaces

## Requirements Analysis

- Attributes
- Operations without parameters and types

Account
Amount
AccountId
Deposit( )
Withdraw( )
GetBalance( )

## Detailed Design

- Visibility
- Signatures
- Contracts

Account
-Amount: int
#AccountId: int
+Deposit( a: int )
+Withdraw( a: int )
+GetBalance( ): int

<<precondition>>  
a >= 0

# Information Hiding

- Definition

*Information hiding is a technique for reducing the dependencies between modules:*


- *The intended client is provided with all the information needed to use the module **correctly**, and **with nothing more***
- *The client uses only the (publicly) available information*

## Visibility Information

- UML defines **three levels of visibility**
  - Similar to C++, Java, and C#
- Private (**implementation interface**): “–”
  - Private features can be accessed only by the class in which they are declared (not even subclasses)
- Protected (**subclass interface**): “#”
  - Protected features can be accessed by the class in which they are defined and by any descendent of the class
- Public (**client interface**): “+”
  - Public features can be accessed by any class

# Implementation of UML Visibility in Java

Account
-Amount: int
#AccountId: int
+Deposit( a: int )
+Withdraw( a: int )
+GetBalance( ): int




```
class Account {  
    private int amount;  
    protected int accountId;  
  
    public void deposit( int a )    {...}  
    public void withdraw( int a )  {...}  
    public int getBalance( )       {...}  
}
```

- **protected** has a slightly different meaning in Java
  - Also visible to classes in the same package
- Eiffel provides more fine-grained visibility control

## Information Hiding Heuristics



- Public interface for classes and subsystems
  - Use the facade pattern
  - Define abstract interfaces that mediate between system and external world as well as between subsystems
- The less an operation knows the less likely it will be affected by any changes
- Access attributes only via operations
  - Only the operations of a class should manipulate its attributes (no public attributes)
  - Trade-off: Information hiding vs. efficiency

# UML is not Enough



- Urs is married to Sile, Sile is married to Beat, and Beat is not married at all
- A valid instantiation of the class diagram!
- Associations describe relations between classes

## UML is not Enough (cont'd)



- Urs is married to Sile, who is only eleven
- A valid instantiation of the class diagram!
- Class diagrams do not restrict values of attributes

# Expressing Contracts

- Natural language
  - Advantage: Easy to understand and use
  - Disadvantage: Ambiguous
- Mathematical notation
  - Advantage: Precise
  - Disadvantage: Difficult for normal customers
- Contract language
  - Formal, but easy to use
  - Examples: Eiffel, JML

spouse expresses  
“is married to”

spouse: Person  $\rightarrow$  Person  
 spouse = spouse<sup>-1</sup>  
 spouse  $\cap$  id =  $\emptyset$

$\forall p: \text{Person}: p \in \mathbf{dom}(\text{spouse}) \Rightarrow$   
 spouse( p )  $\in \mathbf{dom}(\text{spouse}) \wedge$   
 p  $\neq$  spouse( p )  $\wedge$   
 p = spouse( spouse( p ) )

spouse  $\neq$  **Void** implies  
 spouse  $\neq$  **Current** and  
 spouse.spouse = **Current**

# Contracts in Eiffel: Object Invariants

- Associated with classes
- Describe **consistency criteria** of objects and object structures
- Hold for all instances of a class

```
class PERSON feature
```

```
age: INTEGER  
spouse: PERSON
```

```
invariant
```

```
spouse /= Void
```

```
implies
```

```
spouse /= Current
```

```
and
```

```
spouse.spouse = Current
```

```
and
```

```
age >= 16
```

```
end -- class PERSON
```

# Object Constraint Language – OCL

- The contract language for UML
  
- Used to specify
  - Invariants of objects
  - Pre- and postconditions of operations
  - Guards (for instance, in state diagrams)
  
- Special support for
  - Navigation through UML class diagram
  - Associations with multiplicities

## Form of OCL Invariants

- Constrains can mention
  - **self**: the contextual instance
  - Attributes and role names
  - Side-effect free methods (stereotype <<query>>)
  - Logical connectives
  - Operations on integers, reals, strings, sets, bags, sequences
  - Etc.


The context is an instance of a class in the UML diagram

Declares an invariant

```
context Person inv:  
self.age >= 0
```

A boolean constraint

# OCL Invariants: Example




- A savings account has a non-negative balance
- Checking accounts are owned by adults

**context SavingsAccount inv:**  
**self.amount >= 0**

**context CheckingAccount inv:**  
**self.owner.age >= 18**

# OCL Invariants: Contexts



- Checking accounts are owned by adults

**context** CheckingAccount **inv:**  
**self.owner.age** >= 18

- Accounts are owned by adults

**context** Account **inv:**  
**self.owner.age** >= 18

- Customers are adults

**context** Customer **inv:**  
**self.age** >= 18

# Collections

- OCL provides three predefined collection types
  - Set, Sequence, Bag
- Common operations on collections


size( )	Number of elements in the collection
includes( object )	True iff the object is an element
isEmpty( )	True iff collection contains no elements
exists( expression )	True iff expression is true for at least one element
forAll( expression )	True iff expression is true for all elements

# Generating Collections


- Explicitly enumerating the elements
- By navigating along 1:n associations
  - Navigation along a single 1:n association yields a Set
  - Navigation along a single 1:n association labeled with the constraint { ordered } yields a Sequence

```
Set { 1, 7, 16 }
```

```
self.accounts
```



# Example: Multiplicity Zero or One




**self** can be omitted

spouse used as set

**context Person inv:**  
 spouse->size( ) = 1 **implies**  
 age >= 16 **and** spouse.spouse = **self** **and** spouse <> **self**

spouse used as object

# Example: Quantification and Type Information




**context** Customer **inv:**  
 age  $\leq$  18 **implies**  
 accounts  $\rightarrow$  forAll( a | a.oclIsKindOf( SavingsAccount ) )

Subtype  
relation

$\forall a \in \text{accounts}: a.\text{oclIsKindOf}(\text{SavingsAccount})$

# Example: Composite Pattern



- A composite is the parent of its components
- A component is contained in its parent composite

**context Composite inv:**  
 children->forall( c | c.parent = **self** )

**context Component inv:**  
 parent->size( ) = 1 **implies**  
 parent.children->includes( **self** )

# Contracts in Eiffel: Method Specifications

- Method precondition
  - Must be true before the method is executed
- Method postcondition
  - Must be true after the method terminates
  - old expressions is used to refer to values of the pre-state

```
class interface ACCOUNT feature
```

```
  withdraw ( a: INTEGER ) is
```

```
    require a >= 0
```

```
    ensure GetBalance( ) = old( GetBalance( ) – a )
```

```
end
```

# Pre- and Postconditions in OCL

Context specifies  
method signature


```
context Account::Withdraw( a: int )  
pre:  a >= 0  
post: GetBalance( ) = GetBalance@pre( ) - a
```

Suffix @pre is  
used to refer to  
prestate values

- **result** is used to refer to return value
- Pre- and postconditions can be named (like in Eiffel)

## Alternative Notation

- Contracts can be depicted as notes in diagrams
  - Stereotypes instead of keywords **inv**, **pre**, **post**



# 5. Detailed Design

## 5.1 Overview

## 5.2 Reuse


### 5.2.1 Design Patterns

### 5.2.2 Case Study: Patterns in the Java AWT

## 5.3 Interface Specification

## 5.4 Object Model Restructuring and Optimization


# Object Model Restructuring and Optimization



## Increasing Inheritance


- **Rearrange** and **adjust** classes and operations to prepare for inheritance
  - Generalization
  - Specialization
- **Generalization** is a common modeling activity
  - Abstracts common behavior out of a group of classes
  - If operations or attributes are repeated in 2 classes the classes might be instances of a more general class
- Superclasses are desirable
  - Increase of modularity, extensibility, and reusability

# Increasing Inheritance: Example



# Collapsing Classes

- Collapse a **class** without interesting behavior **into an attribute**
  - If the only operations defined on the attributes are Set( ) and Get( )




- Associations are more flexible than attributes but often introduce unnecessary indirection


# Optimizing Access Paths

- Add **redundant associations** to minimize access cost
  - What are the most frequent operations?
  - How often is the operation called? (30 times a month, every 50 ms)
- Turn classes into attributes (collapse classes)

# Caching Complex Computations



- ShortestPath is an expensive operation
- Result can be cached



## Keeping Caches Up-to-Date: Eager Update

- Operations that change the state of the data structure **update the cache**
- Possible if cache update is cheap or state changes are rare
- Also called push solution

```
void addEdge( Node n, Node m ) {  
    // add (n,m) to edges  
    sp = computeShortestPath( );  
}  
  
Path shortestPath( ) {  
    return sp;  
}
```

## Keeping Caches Up-to-Date: Lazy Update

- Operations that change the state of the data structure **increment a version counter** or set a flag
- Access to cached value updates cache if cache is outdated
- Also called pull solution

```
void addEdge( Node n, Node m ) {  
    // add (n,m) to edges  
    sp = null; // invalidate cache  
}  
  
Path shortestPath( ) {  
    if ( sp == null )  
        sp = computeShortestPath( );  
    return sp;  
}
```

# Keeping Caches Up-to-Date: Active Values

- Observer pattern
  - Active value is subject
  - Cache is observer
- Operations that change the state of the data structure **trigger an event** (notify)
- Cache can be updated eagerly or lazily


```
void addEdge( Node n, Node m ) {  
    // add (n,m) to edges  
    notify( ); // trigger event  
}
```

```
void update( ) { // eager update  
    sp = computeShortestPath( );  
}
```

```
Path shortestPath( ) {  
    return sp;  
}
```

# Delaying Complex Computations

- Computation is delayed until result is accessed
- Example: lazy object initialization



# Design Optimizations: Summary

- Design optimizations are an important part of the detailed design phase
  - The requirements analysis model is semantically correct but often too inefficient if directly implemented
  - Strike a balance between efficiency and clarity

