

Konzepte objektorientierter Programmierung

– Lecture 11 –

Prof. Dr. Peter Müller
Software Component Technology

Wintersemester 05/06

Meeting the Requirements

Cooperating Program Parts
with Well-Defined Interfaces

- Objects (data + code)
- Interfaces
- Encapsulation

Classification and
Specialization

- Classification, subtyping
- Polymorphism
- Substitution principle

Inherently
Concurrent
Execution Model

- Active objects
- Message passing

Correctness

- Interfaces
- Encapsulation
- Simple, powerful concepts

Agenda for Today

11. Interface Specifications

11.1 Contracts

11.2 Semantics of Interface Specifications

11.3 Model-Based Specifications

11.4 A Closer Look at Modifies Clauses

Objectives

- Specification techniques
- Description of component behavior

Correctness

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    ...  
  
    public void insert( int i ) {  
        for ( int j = 0; j < next; j-- )  
            if array[ j ] == i then return true;  
        return false;  
    }  
}
```


Behavioral Specification

Semantic Rules

Context Conditions

Syntax Rules

Aspects of Correctness



Test and Verification

Test

- Objective
 - Detect bugs
- Examples
 - White box test
 - Black box test
- Problems
 - Successful test does not guarantee correctness

Verification

- Objective
 - Prove correctness
- Examples
 - Formal verification based on a logic
 - Symbolic execution
- Problems
 - Expensive
 - Formal specification of behavior is required

11. Interface Specifications

11.1 Contracts

11.2 Semantics of Interface Specifications

11.3 Model-Based Specifications

11.4 A Closer Look at Modifies Clauses

Pre-Post Specifications

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    public boolean has( int i ) {  
        for ( int j = 0; j < next; j++ )  
            if ( array[ j ] == i ) return true;  
        return false;  
    }  
    private void resize( ) {  
        int[ ] tmp = new int[ array.length + 10 ];  
        System.arraycopy( array, 0, tmp, 0,  
            array.length );  
        array = tmp;  
    }  
}
```

```
// requires !has( i )  
// ensures has( old( i ) )  
public void insert( int i ) {  
    if ( next == array.length )  
        resize( );  
    array[ next ] = i;  
    next++;  
}  
...
```

Frame Properties

```
// requires !has( i )
// ensures has( old( i ) )
public void insert( int i ) {
    array[ 0 ] = i;
    next = 1;
}
```

```
Set s = new ArraySet( );
s.insert( 42 );
s.insert( 1492 );
boolean b = s.has( 42 );
```

```
// requires !has( i )
// ensures has( old( i ) ) &&
//    $\forall j: \text{old}( \text{has}( j ) ) \Rightarrow \text{has}( j )$ 
public void insert( int i ) { ... }
```


- Methods can have side-effects
- Frame properties describe **what is left unchanged** by a method execution

Frame Properties (cont'd)

```
// requires !has( i )
// ensures has( old( i ) ) &&
//   ∀j: old( has( j ) ) ⇒ has( j )
public void insert( int i ) { ... }
```

```
void foo( Set s, StringBuffer b ) {
    b.insert( 0, "Hello" );
    s.insert( 1492 );
    System.out.println( b );
}
```

```
class MySet extends ArraySet {
    StringBuffer label;
    public void insert( int i ) {
        label.insert( 0, "Surprise" );
        super.insert( i );
    }
}
```



Modifies Clauses

- In **modular programs**, not all locations that remain unchanged are known
- **Modifies clauses** specify which locations **may be modified** by a method
- Locations **not mentioned** in the modifies clause **must remain unchanged**

```
// requires !has( i )
// ensures has( old( i ) ) &&
//   ∀j: old( has( j ) ) ⇒ has( j )
// modifies array[ next ], next,
//           array
public void insert( int i ) {
    if ( next == array.length )
        resize();
    array[ next ] = i;
    next++;
}
```

Example Revisited

```
// requires !has( i )
// ensures has( old( i ) ) &&
//  $\forall j: \text{old}( \text{has}( j ) ) \Rightarrow \text{has}( j )$ 
// modifies array[ next ], next, array
public void insert( int i ) { ... }
```

```
void foo( Set s, StringBuffer b ) {
    b.insert( 0, "Hello" );
    s.insert( 1492 );
    System.out.println( b );
}
```

```
class MySet extends ArraySet {
    StringBuffer label;
    public void insert( int i ) {
        label.insert( 0, "Surprise" );
        super.insert( i );
    }
}
```

- **Behavioral subtyping:** Subtype methods have to satisfy modifies clauses of overridden supertype methods

Object Invariants

- Object invariants describe **consistency criteria** for objects
- **Invariants** have to hold in all states, in which an object can be accessed by other objects
- Invariants refer to **one execution state**

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // invariant array != null &&  
    // 0 <= next <= array.length  
  
    public void insert( int i ) {  
        if ( next == array.length )  
            resize( );  
        array[ next ] = i;  
        next++;  
    }  
    ...  
}
```

History Constraints

- History constraints relate **two succeeding execution states**
- History constraints enable **datatype induction**

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
    // constraint old( array.length ) <= array.length  
    private void resize( ) {  
        int[ ] tmp = new int[ array.length + 10 ];  
        ...  
    }  
    ...  
}
```

```
class Person {  
    private int age;  
    // constraint old( age ) <= age  
    ...  
}
```

11. Interface Specifications

11.1 Contracts

11.2 Semantics of Interface Specifications

11.3 Model-Based Specifications

11.4 A Closer Look at Modifies Clauses

Hoare Triples

- Like programs, specifications need a well-defined semantics
- Semantics of specifications can be defined in terms of **Hoare triples**

$$\{ P \} m(\dots) \{ Q \}$$

- **Total correctness**: If **P** holds in the prestate of an execution of method **m**, then **m** terminates in a state in which **Q** holds
- **Partial correctness**: If **P** holds in the prestate of an execution of method **m** and **m** terminates, then **Q** holds in the poststate of the execution

Assuming Invariants

- Methods have to **assume the invariant of this** to hold in the prestate
- Methods have to **assume that invariant of all allocated objects** to hold in the prestate

```
// requires !has( i )
public void insert( int i ) {
    if ( next == array.length )
        resize();
    array[ next ] = i;
    next++;
}
```

```
class Client {
    ArraySet as;
    // requires !as.has( 5 )
    public void foo( ) {
        as.insert( 5 );
    }
}
```

Notation

- $\text{inv}_T(o)$ denotes the invariant of class T for object o

```
class Redundant {  
    private int a, b;  
    // invariant this.a == this.b  
    ...  
}
```

$$\text{inv}_{\text{Redundant}}(o) \equiv o.a == o.b$$

- INV_T denotes the conjunction of the invariant of class T for all allocated T-objects

$$\text{INV}_T \equiv \forall o: \text{allocated}(o) \wedge \text{type}(o) <: T \Rightarrow \text{inv}_T(o)$$

Semantics of Pre-Post Specifications

- Each method m may **assume** in the prestate of its executions
 - **The invariants of all allocated objects**
 - **The conjunction of m 's preconditions, P**
- The method must **guarantee** in the poststate
 - **The conjunction of its postconditions, Q**

$$\{ P \wedge \forall S: INV_S \} m(\dots) \{ Q \}$$

Semantics of Modifies-Clauses

- Each method m may **modify**
 - Locations mentioned in its **modifies clause**, M
 - Locations of newly allocated objects
- All other locations have to be left unchanged
 - Temporary modifications are possible

$$\begin{array}{c} \{ P \wedge \forall S: \text{INV}_S \} \\ m(\dots) \\ \{ \forall x, f: [x, f] \in M \vee \neg \text{old}(\text{allocated}(x)) \vee x.f == \text{old}(x.f) \} \end{array}$$

Modifies Clauses: Example

```
// modifies array[ next ], next,  
//           array  
public void insert( int i ) {  
    if ( next == array.length )  
        resize( );  
    array[ next ] = i;  
    next++;  
}
```

```
// modifies array  
private void resize( ) {  
    int[ ] tmp = new int[ array.length + 10 ];  
    System.arraycopy( array, 0, tmp, 0,  
                      array.length );  
    array = tmp;  
}
```

- insert modifies directly
 - this.array[this.next], this.next
- insert modifies indirectly via invocation of resize
 - this.array
 - Locations of newly allocated array

Semantics of Invariants

- Invariants have to **hold in pre- and poststates** of method executions, but can be temporarily violated in between

```
class Redundant {  
    private int a, b;  
    // invariant a == b  
    public void set( int v ) {  
        // invariant holds  
        a = v;  
        // invariant violated  
        b = v;  
        // invariant holds  
    }  
}
```

$$\{ P \wedge \forall S: INV_S \} m(\dots) \{ \forall S: INV_S \}$$

Verification of Invariants

- Assumption: The invariant of class T refers to **private attributes of T-objects only**
- We have to prove that each method or constructor of class T **guarantees the invariant of class T for all allocated T-objects** in the poststate

$$\{ P \wedge \forall S: INV_S \} m(\dots) \{ INV_T \}$$

- Invariants are difficult for object structures with aliasing (see Lecture 4)

11. Interface Specifications

11.1 Contracts

11.2 Semantics of Interface Specifications

11.3 Model-Based Specifications

11.4 A Closer Look at Modifies Clauses

Observer Methods

```
// requires  ∀j. 0 <= j < next: array[ j ] != i  
// ensures   array[ old( next ) ] == old( i )  &&  
//           ∀j. 0 <= j < next: old( array[ j ] ) == array[ j ]  
public void insert( int i ) { ... }
```

```
// requires !has( i )  
// ensures  has( old( i ) ) && ∀j: old( has( j ) ) ⇒ has( j )  
public void insert( int i ) { ... }
```

- Observer methods enable **implementation-independent specifications**
 - Information hiding
 - Exchange of implementations

Problems of Observer Methods

- Observer methods can be specified
 - By other observer methods or
 - By referring to the implementation
- No well-defined implementation-independent specification for observer methods

```
class ArraySet implements Set {  
    // requires true  
    // ensures ∃j. 0 <= j < next:  
    //           array[ j ] == i  
    public boolean has( int i ) { ... }  
    ...  
}
```

```
interface Set {  
    // requires true  
    // ensures ??  
    public boolean has( int i );  
    public void insert( int i );  
}
```

Excursus: Abstract Datatypes

- Abstract datatypes describe datatypes without giving an implementation
- Laws (axioms) can be used to define the semantics of the datatype
- See M. Wirsing: *Algebraic Specification*. In: J. van Leeuwen: *Handbook of Theoretical Computer Science*, Volume B. Elsevier, 1990.


```
datatype Nat  
functions:  
  0:      → Nat  
  succ:   Nat → Nat  
laws:  
  L1: succ(n)=succ(m) ⇒ n=m  
  L2: succ(n)≠0  
  L3: 0∈S ∧ (n∈S ⇒ succ(n)∈S)⇒  
       ∀x: x∈S  
end
```

Example: Abstract Datatype Set


```
datatype Set  
uses: Card, Bool  
functions:  
    empty: → Set  
    member: Set × Card → Bool  
    add: Set × Card → Set  
laws:  
    L1: ¬member( empty, i )  
    L2: member( add( S, i ), i )  
    L3: add( add( S, i ), i ) = add( S, i )  
    L4: add( add( S, i ), j ) = add( add( S, j ), i )  
end
```

Abstraction Functions

- Specify interfaces in terms of the **mathematical vocabulary** provided by abstract datatypes
 - Abstract datatype serves as **model** for the implementation (**two-tiered specifications**)
- Relate object (structures) to terms of the abstract datatypes by **abstraction functions** [Hoare 72]



Example: Abstraction Function



`aS: Object → Set`

`aS(X) = aA(X.array, 0, X.next)`

`aA: Object × Card × Card → Set`

$n \geq 1 \Rightarrow aA(X, n, 1) = \text{empty}$

$n < 1 \Rightarrow aA(X, n, 1) = \text{add}(aA(X, n+1, 1), X[n])$

Example: Interface Specification

```
interface Set {  
    // requires true  
    // ensures result = member( as( this ),i )  
    public boolean has( int i );  
  
    // requires  $\neg$ member( as( this ),i )  
    // ensures as( this ) = add( old( as( this ) ),old( i ) )  
    public void insert( int i );  
}
```

- Abstraction functions omitted for **boolean** and **int**
 - aB: boolean → Bool
 - aI: int → Card

Discussion

- Abstract datatypes
 - Enable **implementation-independent** specifications, especially of interfaces and observer methods
 - Preserve **information hiding** in specifications
 - Are mathematically **precise**
- Problems of two-tiered specifications
 - Programmers have to know programming and specification language
 - Specifications are **not executable** (for instance for testing)

Model Classes

- Description of abstract datatypes **in the programming language**
- Very **simple semantics**
 - No side-effects
 - No sharing
 - Performance is not important
- Real implementations are **specified based on model classes**
- Approach is used in the Java Modeling Language JML (see www.jmlspecs.org)

Model Class Example


```
public /*@ pure @*/ abstract class ModelSet {  
  
    /** Is the argument equal to one of the values in the set. */  
    public abstract boolean member( int elem );  
  
    /** Returns a new set that contains all the elements of  
     *  this and also the given argument. */  
    public abstract ModelSet add( int elem );  
}
```

Model Classes: Laws

```
public /* pure */ abstract class ModelSet {  
  
    // invariant  $\forall \text{int } e1, e2. \text{equational\_theory}( \text{this}, e1, e2 )$   
  
    /* ensures result  $\Leftrightarrow !(\text{new ModelSet( )}).\text{member}( e1 )$   
     * && s.add( e1 ).member( e1 )  
     * && s.add( e1 ).add( e2 ).equals( s.add( e2 ).add( e1 ) )  
     * && s.add( e1 ).add( e1 ).equals( s.add( e1 ) ) */  
    static public pure model boolean  
        equational_theory( ModelSet s, int e1, int e2 );  
}
```

Model Attributes

- Link implementations to models
- Are not part of the state of an object



- May only be used in specifications

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // public model ModelSet abs  
  
    // requires true  
    // ensures result == abs.member( i )  
    public boolean has( int i ) { ... }  
  
    // requires !abs.member( i )  
    // ensures abs.equals( old(abs.add( i )) )  
    public void insert( int i ) { ... }  
    ...  
}
```

Abstraction Functions for Model Classes

- Abstraction functions can be expressed in Java
- represents clauses define the values of model attributes

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // public model ModelSet abs  
    // private represents abs ← aS()  
  
    /* private model ModelSet aS() {  
        ModelSet res = new ModelSet();  
        for ( int j = 0; j < next; j++ )  
            res = res.add( array[ j ] );  
        return res;  
    } */  
  
    ...  
}
```

Specification of Interfaces

- Model attributes may be declared in interfaces
- represents clauses are added in subclasses

```
interface Set {  
    // public model ModelSet abs  
  
    // requires true  
    // ensures result == abs.member( i )  
    public boolean has( int i );  
  
    // requires !abs.member( i )  
    // ensures abs.equals( old( abs.add( i ) ) )  
    public void insert( int i );  
}
```

11. Interface Specifications

11.1 Contracts

11.2 Semantics of Interface Specifications

11.3 Model-Based Specifications

11.4 A Closer Look at Modifies Clauses

Frame Properties Revisited

- Enumerating modifiable locations **violates information hiding**
- Enumerating modifiable locations **does not work for interfaces**

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // modifies array[ next ], next, array  
    public void insert( int i ) { ... }  
  
    ...  
}
```

```
interface Set {  
    // modifies ??  
    public void insert( int i );  
}
```

Extended State Problem

- **Behavioral subtyping**
requires subtype methods to satisfy modifies clauses of supertype methods
- **But:** Subtype methods must have the right to modify the **extended state**

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // modifies array[ next ], next, array  
    public void insert( int i ) { ... }  
  
    ...  
}
```

```
class MaxSet extends ArraySet {  
    private int max;  
  
    public void insert( int i ) {  
        if ( i > max ) max = i;  
        super.insert( i );  
    }  
}
```

Modifies Clauses with Model Attributes

- Model attributes can be used in modifies clauses
- **Rule:** Right to modify model location includes right to modify all normal locations that are needed to compute the value of the model location

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // public model ModelSet abs  
  
    // modifies abs  
    public void insert( int i ) { ... }  
    ...  
}
```

Dependencies

- “*locations that are needed to compute the value of the model location*” are declared by **depends clauses**
- Depends clauses can be private

```
class ArraySet implements Set {  
    private int[ ] array;  
    private int next;  
  
    // public model ModelSet abs  
    // private depends abs ←  
    //           array[ * ], next, array  
  
    // modifies abs  
    public void insert( int i ) { ... }  
    ...  
}
```

Solution

- **Interfaces:** Model attributes can be declared in interfaces
- **Information hiding:** Model attributes are public and do not reveal implementation details
- **Extended state:**
Subclasses can add new depends clauses for attributes of extended state

```
class MaxSet extends ArraySet {  
    private int max;  
    // private depends abs ← max  
    ...  
}
```

Summary

- Interface specification
 - For objects: Invariants and history constraints
 - For methods: Pre-post specifications and modifies clauses
- Model-based specifications
 - Two-tiered: Implementation + algebraic specification
 - One-tiered: Implementation + model classes
 - Abstraction functions or model attributes to relate implementations to models